

Safety	y Data Sheet dated 6/2/2023, version 1
ECTION 1: Identification	of the substance/mixture and of the company/undertakin
1.1. Product identifier	
Mixture identification:	
Trade name: Trade code:	EUGREENSTOU 15W/40 REULA-532
1.2. Relevant identified use Recommended use:	es of the substance or mixture and uses advised against
Agricultural Engine M	otor Oil
1.3. Details of the supplier	of the safety data sheet
Company:	
RILUB S.p.A.	
Via FF. SS. 139	
80044 Ottaviano (NA) Tel. (+39) 081 338341	
	ble for the safety data sheet:
infolab@rilub.it	·
1.4. Emergency telephone (Poison Control Center	number r: Az. Osp. "A. Cardarelli" Naples - Tel. 081 5453333
F DISON CONTROL CENTER	$\mathbf{A}_{\mathbf{A}} = \mathbf{A}_{\mathbf{A}} = $
	ECTION 2: Hazards identification
2.1. Classification of the su	
	t can cause eye and skin irritation.
	2 are referred to the product in the finished form. product is used in water emulsion.
EC regulation criteria 1272/2	
	it. 2, Causes serious eye irritation.
	it. 2, Gauses serious eye initation.
Aquatic Chronic 3, H	Harmful to aquatic life with long lasting effects.
Adverse physicochemical, h	uman health and environmental effects:
No other hazards	
2.2. Label elements Hazard pictograms:	
•	
Warning	
Hazard statements:	
H319 Causes serious	
	atic life with long lasting effects.
Precautionary statements:	ughly ofter handling
P264 Wash Thorou P273 Avoid release to	
	gloves/protective clothing/eye protection/face protection/hearing
protection/	
P337+P313 If eye irrit	ation persists: Get medical advice/attention.
	ents/container in accordance with applicable regulations.
Special Provisions:	
None	



Special provisions according to Annex XVII of REACH and subsequent amendments: Restricted to professional users.

Other I

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1% Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

N.A.

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb	er	Classification
>= 1% - < 2.5%	ALCHILDITIOFOSFAT O DI ZINCO	CAS: EC:	68649-42-3 272-028-3	3.2/2 Skin Irrit. 2 H315
12.070			01-21196579	🤣 3.3/1 Eye Dam. 1 H318
			73-23-0000	4.1/C2 Aquatic Chronic 2
				H411
>= 0.5% - < 1%	Calcium long-chain alkaryl sulfonate			4.1/C2 Aquatic Chronic 2
- < 170	alkal yr Sulforlate			H411
				3.2/2 Skin Irrit. 2 H315
390 ppm	phenol, (tetrapropenyl) derivatives	Index number:	604-092-00-9	
	denvalives	CAS:	74499-35-7	🤣 3.2/1C Skin Corr. 1C H314
				🤣 3.3/1 Eye Dam. 1 H318
				4.1/A1 Aquatic Acute 1 H400
				M=10.
				4.1/C1 Aquatic Chronic 1
				H410 M=10.

SECTION 4: First aid measures

In case of skin contact:

Injuries due to high pressure jets require a prompt surgical intervention and possibly a steroids therapy, to minimize tissue damage and loss of functions.

Every substance, in case of accidents with high pressure pipes or similar, can be accidentaly injected under skin tissue, even without external noticeable skin damage. In this case it's necessary to bring the injured as soon as possible to the hospital for required treatment. Remove contaminated clothes.

Remove contaminated clothes after having started washing of affected body parts and wash thoroughly with water and soap. Immediately call a doctor if necessary.

During usage of high pressure equipment, injection of the product under the skin is possible. In case of injuries due to high pressure jets, injured should be immediately accompanied to the hospital. Don't wait for symptoms to appear.

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap. Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediatley and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.



In d	case of eyes contact:
	Wash eyes immediately with plenty of water for some minute leaving eyelids open.
	Immediately call a doctor if pain and redness persists.
	Wash eyes immediately with plenty of water for some minute leaving eyelids open.
	Immediately call a doctor.
	After contact with the eyes, rinse with water with the eyelids open for a sufficient length of
	time, then consult an opthalmologist immediately.
	Protect uninjured eye.
In a	case of Ingestion:
	Do not under any circumstances induce vomiting.
	OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.
In a	case of Inhalation:
	In case of exposition to high concentration of vapours and mist remove person from the
	contaminated area and move to a well ventilated place.
	Call for medical attention if necessary.
	In case of exposition to high concentration of vapours and mist remove person from the
	contaminated area, move to a well ventilated place and ask for medical attention.
	Remove casualty to fresh air and keep warm and at rest.
4.2	Nost important symptoms and effects, both acute and delayed
	None
4.3	indication of any immediate medical attention and special treatment needed
	In case of accident or unwellness, seek medical advice immediately (show directions for use
	or safety data sheet if possible).
	Treatment:
	In case of exposition to high concentration of vapours and mist remove person from the
	contaminated area and move to a well ventilated place.
	Call for medical attention if necessary.
	Call for medical allention in necessary.
	SECTION 5: Eirofighting modeuroe
	SECTION 5: Firefighting measures
5.1.	Extinguishing media
5.1.	Extinguishing media Suitable extinguishing media:
51.	Extinguishing media Suitable extinguishing media: Use class B fire extinguishing media: carbon dioxide, dry chemical powder, foam, sand, earth.
5.1.	Extinguishing media Suitable extinguishing media: Use class B fire extinguishing media: carbon dioxide, dry chemical powder, foam, sand, earth. Water.
5.1.	Extinguishing media Suitable extinguishing media: Use class B fire extinguishing media: carbon dioxide, dry chemical powder, foam, sand, earth. Water. Carbon dioxide (CO2).
5.1.	Extinguishing media Suitable extinguishing media: Use class B fire extinguishing media: carbon dioxide, dry chemical powder, foam, sand, earth. Water. Carbon dioxide (CO2). Extinguishing media which must not be used for safety reasons:
511	Extinguishing media Suitable extinguishing media: Use class B fire extinguishing media: carbon dioxide, dry chemical powder, foam, sand, earth. Water. Carbon dioxide (CO2). Extinguishing media which must not be used for safety reasons: Avoid usage of water jets. Use water only to cool the surface of the container exposed to fire.
51	Extinguishing media Suitable extinguishing media: Use class B fire extinguishing media: carbon dioxide, dry chemical powder, foam, sand, earth. Water. Carbon dioxide (CO2). Extinguishing media which must not be used for safety reasons:
5.2	Extinguishing media Suitable extinguishing media: Use class B fire extinguishing media: carbon dioxide, dry chemical powder, foam, sand, earth. Water. Carbon dioxide (CO2). Extinguishing media which must not be used for safety reasons: Avoid usage of water jets. Use water only to cool the surface of the container exposed to fire. None in particular. Special hazards arising from the substance or mixture
5.1	 Extinguishing media Suitable extinguishing media: Use class B fire extinguishing media: carbon dioxide, dry chemical powder, foam, sand, earth. Water. Carbon dioxide (CO2). Extinguishing media which must not be used for safety reasons: Avoid usage of water jets. Use water only to cool the surface of the container exposed to fire. None in particular. Special herards ansing from the substance or mixture Avoid to breathe combustion smoke, because, as a result of fire, chlorine, sulfur, nitrogen and
5.1.	 Extinguishing media Suitable extinguishing media: Use class B fire extinguishing media: carbon dioxide, dry chemical powder, foam, sand, earth. Water. Carbon dioxide (CO2). Extinguishing media which must not be used for safety reasons: Avoid usage of water jets. Use water only to cool the surface of the container exposed to fire. None in particular. Opecial hexards arising from the substance or mixture Avoid to breathe combustion smoke, because, as a result of fire, chlorine, sulfur, nitrogen and unburnt hydrocarbons compounds can be formed, as long as other potentially dangerous
5.1.	 Extinguishing media Suitable extinguishing media: Use class B fire extinguishing media: carbon dioxide, dry chemical powder, foam, sand, earth. Water. Carbon dioxide (CO2). Extinguishing media which must not be used for safety reasons: Avoid usage of water jets. Use water only to cool the surface of the container exposed to fire. None in particular. Special hexards arising from the substance or mixture Avoid to breathe combustion smoke, because, as a result of fire, chlorine, sulfur, nitrogen and unburnt hydrocarbons compounds can be formed, as long as other potentially dangerous compounds.
5.1.	 Extinguishing media Suitable extinguishing media: Use class B fire extinguishing media: carbon dioxide, dry chemical powder, foam, sand, earth. Water. Carbon dioxide (CO2). Extinguishing media which must not be used for safety reasons: Avoid usage of water jets. Use water only to cool the surface of the container exposed to fire. None in particular. Special hexards arising from the substance or mixture Avoid to breathe combustion smoke, because, as a result of fire, chlorine, sulfur, nitrogen and unburnt hydrocarbons compounds can be formed, as long as other potentially dangerous compounds. Do not inhale explosion and combustion gases.
5.2	 Extinguishing media Suitable extinguishing media: Use class B fire extinguishing media: carbon dioxide, dry chemical powder, foam, sand, earth. Water. Carbon dioxide (CO2). Extinguishing media which must not be used for safety reasons: Avoid usage of water jets. Use water only to cool the surface of the container exposed to fire. None in particular. Special hexards arising from the substance or mixture Avoid to breathe combustion smoke, because, as a result of fire, chlorine, sulfur, nitrogen and unburnt hydrocarbons compounds can be formed, as long as other potentially dangerous compounds. Do not inhale explosion and combustion gases. Burning produces heavy smoke.
5.2	 Autourshing media: Suitable extinguishing media: Use class B fire extinguishing media: carbon dioxide, dry chemical powder, foam, sand, earth. Water. Carbon dioxide (CO2). Extinguishing media which must not be used for safety reasons: Avoid usage of water jets. Use water only to cool the surface of the container exposed to fire. None in particular. Special hazards arising from the substance of mixture Avoid to breathe combustion smoke, because, as a result of fire, chlorine, sulfur, nitrogen and unburnt hydrocarbons compounds can be formed, as long as other potentially dangerous compounds. Do not inhale explosion and combustion gases. Burning produces heavy smoke. Advice for firefighters
5.2	 Suitable extinguishing media: Use class B fire extinguishing media: carbon dioxide, dry chemical powder, foam, sand, earth. Water. Carbon dioxide (CO2). Extinguishing media which must not be used for safety reasons: Avoid usage of water jets. Use water only to cool the surface of the container exposed to fire. None in particular. Special heards ansing from the substance or mixture Avoid to breathe combustion smoke, because, as a result of fire, chlorine, sulfur, nitrogen and unburnt hydrocarbons compounds can be formed, as long as other potentially dangerous compounds. Do not inhale explosion and combustion gases. Burning produces heavy smoke. Avoice for firengliers Note: Cool with water all the containers not involved in fire but exposed to heat of fire, to
5.2	 Suitable extinguishing media: Use class B fire extinguishing media: carbon dioxide, dry chemical powder, foam, sand, earth. Water. Carbon dioxide (CO2). Extinguishing media which must not be used for safety reasons: Avoid usage of water jets. Use water only to cool the surface of the container exposed to fire. None in particular. Social heards arising from the substance or mixture Avoid to breathe combustion smoke, because, as a result of fire, chlorine, sulfur, nitrogen and unburnt hydrocarbons compounds can be formed, as long as other potentially dangerous compounds. Do not inhale explosion and combustion gases. Burning produces heavy smoke. Avoid to breat all the containers not involved in fire but exposed to heat of fire, to avoid eventual explosion and propagation of fire.
5.2	 Suitable extinguishing media: Use class B fire extinguishing media: carbon dioxide, dry chemical powder, foam, sand, earth. Water. Carbon dioxide (CO2). Extinguishing media which must not be used for safety reasons: Avoid usage of water jets. Use water only to cool the surface of the container exposed to fire. None in particular. Special hearting arising from the substance or mixture Avoid to breathe combustion smoke, because, as a result of fire, chlorine, sulfur, nitrogen and unburnt hydrocarbons compounds can be formed, as long as other potentially dangerous compounds. Do not inhale explosion and combustion gases. Burning produces heavy smoke. Avvice for findighters Note: Cool with water all the containers not involved in fire but exposed to heat of fire, to avoid eventual explosion and propagation of fire. Use suitable breathing apparatus.
5.2	 Suitable extinguishing media: Use class B fire extinguishing media: carbon dioxide, dry chemical powder, foam, sand, earth. Water. Carbon dioxide (CO2). Extinguishing media which must not be used for safety reasons: Avoid usage of water jets. Use water only to cool the surface of the container exposed to fire. None in particular. Social Incords arising from the substance or mixture Avoid to breathe combustion smoke, because, as a result of fire, chlorine, sulfur, nitrogen and unburnt hydrocarbons compounds can be formed, as long as other potentially dangerous compounds. Do not inhale explosion and combustion gases. Burning produces heavy smoke. Advice for filefighters Note: Cool with water all the containers not involved in fire but exposed to heat of fire, to avoid eventual explosion and propagation of fire. Use suitable breathing apparatus. Collect contaminated fire extinguishing water separately.
5.2	 Suitable extinguishing media: Use class B fire extinguishing media: carbon dioxide, dry chemical powder, foam, sand, earth. Water. Carbon dioxide (CO2). Extinguishing media which must not be used for safety reasons: Avoid usage of water jets. Use water only to cool the surface of the container exposed to fire. None in particular. Second Incards ansing from the substance or mixture Avoid to breathe combustion smoke, because, as a result of fire, chlorine, sulfur, nitrogen and unburnt hydrocarbons compounds can be formed, as long as other potentially dangerous compounds. Do not inhale explosion and combustion gases. Burning produces heavy smoke. Avoid eventual explosion and propagation of fire. Use suitable breathing apparatus. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
5.2	 Additional media Suitable extinguishing media: Use class B fire extinguishing media: carbon dioxide, dry chemical powder, foam, sand, earth. Water. Carbon dioxide (CO2). Extinguishing media which must not be used for safety reasons: Avoid usage of water jets. Use water only to cool the surface of the container exposed to fire. None in particular. Social metricular. Avoid to breathe combustion smoke, because, as a result of fire, chlorine, sulfur, nitrogen and unburnt hydrocarbons compounds can be formed, as long as other potentially dangerous compounds. Do not inhale explosion and combustion gases. Burning produces heavy smoke. Avoid eventual explosion and propagation of fire. Use suitable breathing apparatus. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.
5.2	 Suitable extinguishing media: Use class B fire extinguishing media: carbon dioxide, dry chemical powder, foam, sand, earth. Water. Carbon dioxide (CO2). Extinguishing media which must not be used for safety reasons: Avoid usage of water jets. Use water only to cool the surface of the container exposed to fire. None in particular. Second futures ansing from the substance or mixture Avoid to breathe combustion smoke, because, as a result of fire, chlorine, sulfur, nitrogen and unburnt hydrocarbons compounds can be formed, as long as other potentially dangerous compounds. Do not inhale explosion and combustion gases. Burning produces heavy smoke. Avoid eventual explosion and propagation of fire. Use suitable breathing apparatus. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
5.2	 Additional media Suitable extinguishing media: Use class B fire extinguishing media: carbon dioxide, dry chemical powder, foam, sand, earth. Water. Carbon dioxide (CO2). Extinguishing media which must not be used for safety reasons: Avoid usage of water jets. Use water only to cool the surface of the container exposed to fire. None in particular. Social metricular. Avoid to breathe combustion smoke, because, as a result of fire, chlorine, sulfur, nitrogen and unburnt hydrocarbons compounds can be formed, as long as other potentially dangerous compounds. Do not inhale explosion and combustion gases. Burning produces heavy smoke. Avoid eventual explosion and propagation of fire. Use suitable breathing apparatus. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.
5.2	 Suitable extinguishing media: Use class B fire extinguishing media: carbon dioxide, dry chemical powder, foam, sand, earth. Water. Carbon dioxide (CO2). Extinguishing media which must not be used for safety reasons: Avoid usage of water jets. Use water only to cool the surface of the container exposed to fire. None in particular. Social here are are fired from the substance of mixture Avoid to breathe combustion smoke, because, as a result of fire, chlorine, sulfur, nitrogen and unburnt hydrocarbons compounds can be formed, as long as other potentially dangerous compounds. Do not inhale explosion and combustion gases. Burning produces heavy smoke. Avrice for fired phones Note: Cool with water all the containers not involved in fire but exposed to heat of fire, to avoid eventual explosion and propagation of fire. Use suitable breathing apparatus. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely. Full protective suit equipped with respiratory equipment.
5.2.	 Suitable extinguishing media: Use class B fire extinguishing media: carbon dioxide, dry chemical powder, foam, sand, earth. Water. Carbon dioxide (CO2). Extinguishing media which must not be used for safety reasons: Avoid usage of water jets. Use water only to cool the surface of the container exposed to fire. None in particular. Avoid to breathe combustion smoke, because, as a result of fire, chlorine, sulfur, nitrogen and unburnt hydrocarbons compounds can be formed, as long as other potentially dangerous compounds. Do not inhale explosion and combustion gases. Burning produces heavy smoke. Avoide ventual explosion and propagation of fire. Use suitable breathing apparatus. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely. Full protective suit equipped with respiratory equipment.
5.2.	 Suitable extinguishing media: Use class B fire extinguishing media: carbon dioxide, dry chemical powder, foam, sand, earth. Water. Carbon dioxide (CO2). Extinguishing media which must not be used for safety reasons: Avoid usage of water jets. Use water only to cool the surface of the container exposed to fire. None in particular. Social technics are find from the substance or mixture Avoid to breathe combustion smoke, because, as a result of fire, chlorine, sulfur, nitrogen and unburnt hydrocarbons compounds can be formed, as long as other potentially dangerous compounds. Do not inhale explosion and combustion gases. Burning produces heavy smoke. Avoid eventual explosion and propagation of fire. Use suitable breathing apparatus. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely. Full protective suit equipped with respiratory equipment.

REULA-532/1 Page n. 3 of 11



	In case of spillage of relevant quantities, most of all if in confined environment, avoid to breathe vapours and ventilate the environment, or use protective equipment for respiration. Wear personal protection equipment. Remove persons to safety.
	See protective measures under point 7 and 8.
6.2. E	Avoid dispersion of the product and penetration in the soil, in the sewers or in surface water. If necessary inform competent local authorities. Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Retain contaminated washing water and dispose it. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Suitable material for taking up: absorbing material, organic, sand
	In case of spill or leakage: danger of aerosol formation, which may, under appropriate condition of ignition, catch fire. Stem in case of spillage of relevant quantities of product. Contains the spill of little quantities of product with earth, sand or other inert absorbing material. Transfer in appropriate impermeable containers, adequate for storage and transport of recovered material. Dispose according to current regulation. Wash with plenty of water.
	See also section 8 and 13.
	SECTION 7: Handling and storage
7.1. P	recautions for safe handling
7.2.0	Avoid direct contact with the product. Avoid to breathe aerosol or vapours of the product, ensuring an adequate ventilation of workplace, most of all if confined. Don't smoke or use open flames; avoid contact with sparks or possible sources of ignition; do not keep open containers in the workplace, in order to avoid formation of highly concentrated vapours. Avoid contact with skin and eyes, inhalation of vapours and mists. Don't use empty container before they have been cleaned. Before making transfer operations, assure that there aren't any incompatible material residuals in the containers. See also section 8 for recommended protective equipment. Advice on general occupational hygiene: Contamined clothing should be changed before entering eating areas. Do not eat or drink while working.
	Maintain the product in original containers, stored in an environment and conditions such as is possible to ensure control and containment of leakage. Store in a cool place, away from any heat source or possible ignition and from exposure to sun light. Avoid accumulating electrostatic charge. Containers must be maintained closed. Ensure adequate ventilation of the room. Keep away from food, drink and feed. Incompatible materials: None in particular. Instructions as regards storage premises: Adequately ventilated premises.
(.). 0	None in particular
	SECTION 8: Exposure controls/personal protection
L	

REULA-532/1 Page n. 4 of 11



	rol parameters					
Av ap	No specific requirements in normal conditions of use. Avoid generation of mists or aerosol and their diffusion through machine protection (if appropriate) and through the usage of localized ventilation/aspiration. Calcium long-chain alkaryl sulfonate EU - TWA: 5.000 mg/m3					
	DNEL Exposure Limit Values					
	CHILDITIOFOSFA	TO DI ZINCO -		-3 sumer: 4.8 mg/Kg bw/day - Exposure:		
		9 mg/Kg bw/day	- Exposure: Or	al		
PNEC E	posure Limit Value		•			
Ν.						
	sure controls					
Eye prote						
Fo	ear safety glasses or r more information e close fitting safet	refer to UNI-EN	166 standard.	contact with the product.		
Us			terial; change in	nmediately contaminated clothes and		
lt's	sh carefully before advisable to maint r more information	tain good persor				
	e clothing that prov			to the skin, e.g. cotton, rubber, PVC or		
	n for hands:					
re: W	Wear work gloves (for example in neoprene, nitrile or PVC), preferably with inner cover, resistant to mineral oils or solvents. Gloves must be changed when signs of wear are visible. Wear gloves after an adequate cleaning of the hands.					
eq	In case of not prolonged contacts, use of barrier creams may be an useful protection equipment. In case of not prolonged contacts, use of barrier creams may be an useful protection					
eq	uipment.	-		ditions and needs to consider the		
inf Fo	ormation from the s	supplier. refer to UNI-EN	374 standard.			
rul	Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.					
W ad re: ac	Respiratory protection: Whenever operational conditions and other equipment to limit workers exposure will be not adequate to respect exposure limits as specified in section 8, other protective equipments fo respiratory ways are needed: mask with filter for organic vapours and for dusts/mists (e.g. active carbon mask)					
Thermal	Not needed for normal use. Thermal Hazards:					
	None Environmental exposure controls:					
	ne					
Appropria	ate engineering cor ne	ntrols:				
	SECTI					
		<u>ON 9: Physica</u>	I and chemica	al properties		
<u>9.1. Infor</u>	mation on basic p	hysical and ch	emical propert	ies		
9.1. Infor Properti Physical	mation on basic p 98	ON 9: Physica hysical and ch Value liquid	I and chemica emical propert Method:	al properties		



Colour:	amber		
Odour:	caratteristico		
Melting point/freezing point:	-30°C	ASTM D 97	
Boiling point or initial boiling point and boiling range:	Not defined/ Not available		
Flammability:	N.A.		
Lower and upper explosion limit:	Not defined/ Not available		
Flash point:	240°C	ASTM D 92	
Auto-ignition temperature:	Not defined/ Not available		
Decomposition temperature:	Not defined/ Not available		
pH:	Not defined/ Not available		
Kinematic viscosity:	N.A.		
Solubility in water:	Insolubile		
Solubility in oil:	Solubile		
Partition coefficient n-octanol/water (log value):	Not defined/ Not available		
Vapour pressure:	Not defined/ Not available		
Density and/or relative density:	0.870 kg/dm ³	ASTM D 4052	
Relative vapour density:	Not defined/ Not available		
	Particle cha	racteristics:	
Particle size:	N.A.		

Properties	Value	Method:	Notes
Viscosity:	105.0 cSt @ 40°C - 14.0 cSt @ 100°C	ASTM D 445	

SECTION 10: Stability and reactivity

Avoid contact with strong acids and bases and strong oxidizers. Stable under normal conditions.
10.2. Chemical stability
Product is stable to room temperature.
Stable under normal conditions.
10.3. Possibility of hazardous reactions
None
10.4. Conditions to avoid
Stable under normal conditions.
10.5. Incompatible materials
None in particular.
10.6. Hazardous decomposition products
None.



SECTION 44. Toxicological information
SECTION 11: Toxicological information 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2003
Toxicological information of the product:
EUGREENSTOU 15W/40
a) acute toxicity
Not classified
Based on available data, the classification criteria are not met
b) skin corrosion/irritation
Not classified
Based on available data, the classification criteria are not met
c) serious eye damage/irritation
The product is classified: Eye Irrit. 2 H319
d) respiratory or skin sensitisation Not classified
Based on available data, the classification criteria are not met
e) germ cell mutagenicity
Not classified
Based on available data, the classification criteria are not met
f) carcinogenicity
Not classified
Based on available data, the classification criteria are not met
g) reproductive toxicity
Not classified
Based on available data, the classification criteria are not met
h) STOT-single exposure
Not classified
Based on available data, the classification criteria are not met
i) STOT-repeated exposure Not classified
Based on available data, the classification criteria are not met
j) aspiration hazard
Not classified
Based on available data, the classification criteria are not met
Toxicological information of the main substances found in the product:
ALCHILDITIOFOSFATO DI ZINCO - CAS: 68649-42-3
a) acute toxicity:
Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg
Test: LD50 - Route: Oral - Species: Rat 2230 mg/kg
11.2. Information on other hazards Endoaring disrupting properties:
Endocrine disrupting properties: No endocrine disruptor substances present in concentration >= 0.1%
No endocrine disruptor substances present in concentration >= 0.1%
SECTION 12: Ecological information
Adopt good working practices, so that the product is not released into the environment.
EUGREENSTOU 15W/40
The product is classified: Aquatic Chronic 3 - H412
12.2. Persistence and degradability
Although the product is not classified hazardous for the environment, it is believed that it's not
easily biodegradable.
The product sinks in the water (if the density is >1)
The product floats on the water (if density is <1)
Product is easily dispersible in the soil.
Product is easily dispersible in water.



Product is easily absorbed in the soil. Product evaporates and can be easily dispersed in the air. The product floats on the water (if density is <1) Product is adsorbed superficially in the soil. The product evaporates difficultly. ALCHILDITIOFOSFATO DI ZINCO - CAS: 68649-42-3 Biodegradability: Not readily biodegradable
N.A.
Mobility in soil
N.A.
Results of PBT and vPvB assessment
vPvB Substances: None - PBT Substances: None Endocrine disrupting properties
No endocrine disruptor substances present in concentration >= 0.1%
Other adverse effects None
None
SECTION 13: Disposal considerations
Waste treatment methods
Dispose product (and emulsions in case of water-soluble lubrorefrigerants products) and containers sending it to approved companies, paying attention to obligations of DPR n.691 of 23/08/82 (Mandatory consortium for used oils) and Part IV of the Environmental code (D.Lgs. n. 152 of 3/4/2006) and updates Don't discharge in sewers, tunnels or water courses. Follow current legal obligations. Recover if possible. In so doing, comply with the local and national regulations currently in force.
SECTION 14: Transport information
UN number or ID number
Not classified as dangerous in the meaning of transport regulations.
UN proper shipping name
N.A.
Transport hazard class(es)
N.A.
Packing group
N.A.
Environmental hazards
N.A.
Special precautions for user
N.A.
Maritime transport in bulk according to IMO instruments N.A.
SECTION 15: Regulatory information
Safety, health and environmental regulations/legislation specific for the substance or ire
Dir. 98/24/EC (Risks related to chemical agents at work) Dir. 2000/39/EC (Occupational exposure limit values) Regulation (EC) n. 1907/2006 (REACH) Regulation (EC) n. 1272/2008 (CLP) Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

REULA-532/1 Page n. 8 of 11



Regulation (EU) n. 618/2012 (ATP 3 CLP)	
Regulation (EU) n. 487/2013 (ATP 4 CLP)	
Regulation (EU) n. 944/2013 (ATP 5 CLP)	
Regulation (EU) n. 605/2014 (ATP 6 CLP)	
Regulation (EU) n. 2015/1221 (ATP 7 CLP)	
Regulation (EU) n. 2016/918 (ATP 8 CLP)	
Regulation (EU) n. 2016/1179 (ATP 9 CLP)	
Regulation (EU) n. 2017/776 (ATP 10 CLP)	
Regulation (EU) n. 2018/669 (ATP 11 CLP)	
Regulation (EU) n. 2018/1480 (ATP 13 CLP)	
Regulation (EU) n. 2019/521 (ATP 12 CLP)	
Regulation (EU) n. 2020/217 (ATP 14 CLP)	
Regulation (EU) n. 2020/1182 (ATP 15 CLP)	
Regulation (EU) n. 2021/643 (ATP 16 CLP)	
Restrictions related to the product or the substances contained acc	cording to Annex XVII Regulation
(EC) 1907/2006 (REACH) and subsequent modifications:	
Restrictions related to the product:	
Restriction 3 Restrictions related to the substances contained:	
Restrictions related to the substances contained: Restriction 28	
Restriction 30	
Restriction 75	
Where applicable, refer to the following regulatory provisions :	
Directive 2012/18/EU (Seveso III)	
Regulation (EC) nr 648/2004 (detergents).	
Dir. 2004/42/EC (VOC directive)	
D.M. of 13 february 2003: third list of harmonized laws conce	erning the implementation of
directive 89/686/CEE on personal protective equipment. D. I	
implementation of article 1 of Law 3 august 2007, n. 123, on	
the workplace.	
D.M. 14 january 2008: List of diseases for which is mandato	
139 of Testo Unico, approved with decree of the President of	
1965, n. 1124, and subsequent integrations. D.P.R. n. 689 o	
companies and processes subject to control of the Fire prote	
protection. Directive 98/8/CE of 16 february 1998 on placing	of biocidal products on the
market.	
Descriptions related to directive FUL0040/40 (Occurs III))	
Provisions related to directive EU 2012/18 (Seveso III):	
Seveso III category according to Annex 1, part 1	
None	
15.2. Chemical safety assessment	
No Chemical Safety Assessment has been carried out for th	e mixture.
SECTION 16: Other information	
Don't use this product for uses different from those identified. In thi	s case user may be subject to
risk not evaluated.	
This sheet has been compiled in accordance to Guidance on prepa	
lubricants, prepared by the Industrial Group of Lube Companies (G	AIL) - Website:
http://aispec.federchimica.it	
Full text of phrases referred to in Section 3:	
H315 Causes skin irritation.	
H318 Causes serious eye damage.	
H411 Toxic to aquatic life with long lasting effects.	
H360F May damage fertility.	

REULA-532/1 Page n. 9 of 11



H314 Causes severe skin burns and eye damage. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects.

Hazard class and hazard category	Code	Description
Skin Corr. 1C	3.2/1C	Skin corrosion, Category 1C
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Repr. 1B	3.7/1B	Reproductive toxicity, Category 1B
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3

This safety data sheet has been completely updated in compliance to Regulation 2020/878. Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Eye Irrit. 2, H319	Calculation method
Aquatic Chronic 3, H412	Calculation method

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).



IMDG: INCI:	International Maritime Code for Dangerous Goods. International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods
	by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.