



Technical Data Sheet

EPLUS MARE 80W-90

Nautical transmission lubricant

High quality lubricant with marked EP characteristics for the protection of marine transmission systems. Specifically formulated for gearboxes with manual transmission (Mercury, Evinrude, Johnson, Mariner, Chrysler, Suzuki, Yamaha) and for stern drives.

Applications & Benefits

- Long Life Oil

Guarantees longer oil intervals thanks to the new additive technology used. Stability and reliability allow a regular operation of the transmission systems.

- Wear Protection

Improved anti-wear behavior, that is the phenomena of abrasion, scratching and corrosion typical of very loaded differentials, which ensures an extension of the useful life of the differential.

- Low friction coefficient

The low friction coefficient guarantees, together with the stability of the lubricant to the shear phenomena, a lower loss of power at the various operating temperatures.

Specifications & Approvals

- Exceeds the specifications listed below:

API GL-5 API GL-4 EP 90

*For further information please contact the Technical Service.





Chemical-Physical Characteristics

Test	Method	Eplus mare 80W-90
SAE Grade	-	80W-90
Color	Visual	Green
Density @ 15°C, kg/dm ³	ASTM D 4052	0.880
Viscosity cSt @ 40°C cSt @ 100°C	ASTM D 445	125.0 16.0
Viscosity Index - Unit	ASTM D 2270	110
Flash point, °C	ASTM D 92	220
Pour point, °C	ASTM D 97	-30

NOTE: The above values are "typical" for normal production tolerance and do NOT constitute a specification.

Storage, Health & Environment

- Storage & Health

It is recommended to store the EPLUS MARE 80W-90 lubricant indoors. If, by necessity, the storage is carried out outdoors, it is recommended to place the stems, possibly under a roof, in a horizontal position and if kept in a vertical position cover them with a lid to avoid water infiltration. It is advisable not to store the packages at temperatures above 60°C or directly in the sun as it is good to keep them in places not subject to frost. EPLUS MARE 80W-90 does not present health effects when used correctly, applying normal personal hygiene standards.

- Environment

Do not discharge new and/or used lubricant into the sewage system, soil or watercourses. The used lubricant must be delivered to an authorized collection point.

Additional information

- Safety Data Sheet

It is supplied separately and must be considered for the relative information or can be easily downloaded from the website www.rilub.it

For further information contact the technical service:



+390813383413



infolab@rilub.it